

インマイチ

# MOSAIC





Morello<sup>™</sup> Glass and Metal Mosaics from American Olean feature eclectic mosaic blends that exude modern character. Morello's multiple colors and finishes were cultivated to suit every design scheme. An on-trend palette reflects today's sophisticated tastes while the mix of glass and extruded aluminum provide both harmony and contrast.

# 5/8 x 5/8 MOSAIC


METAL & GLASS WALL

MORELLO

ТМ



QUARTZ MM01



MOONSTONE MM02



OBSIDIAN MM03



AMBER MM04



TOPAZ MM05

# 5/8 x RANDOM MOSAIC



QUARTZ MM01



AMBER MM04



MOONSTONE MM02



TOPAZ MM05



### тм MORELLO METAL & GLASS WALL

# SIZES, SHADE VARIATION & PRICING

# 

5/8 x 5/8 MOSAIC (11-7/8" x 11-7/8" Sheet) (30.00 cm x 30.00 cm Sheet)



TILE THICKNESS: 5/16" RECOMMENDED GROUT JOINT: 1/8" RELATIVE PRICING: High

(V4)

#### CLEANING PROCEDURES

- Remove loose dust and dirt with a damp cloth or sponge

- Use a neutral, non-abrasive cleaner suitable for ceramic tile
- Remove cleaning solution with a clean, damp sponge or mop

#### INSTALLATION METHODS BACKING MATERIALS

- Concrete

- Exterior grade plywood - Cementitious backer board

5/8 x RANDOM MOSAIC				

**5/8 x RANDOM MOSAIC** (13-1/4" x 11-7/8" Sheet) (33.66 cm x 30.00 cm Sheet)

> SETTING - Latex modified thin-set

- Ероху

GROUTING

- Unsanded grout - Unsanded cement grout - Epoxy grout

# PERFORMANCE CHARACTERISTICS

	MOISTURE ABSORPTION	BREAKING STRENGTH	MOHS	CHEMICAL RESISTANCE
Mosaic	< 0.5%	>100 lbs.	4.0	Resistant

# APPLICATIONS

	SUITABLE
Walls/Backsplashes	۲
Countertops	$\bigcirc$
Pool Linings	$\bigcirc$

Not recommended for pool use.

Suitable for use in wet areas such as shower walls.

Suitable for exterior applications in freezing and non-freezing climates only when proper installation methods are followed.

# NOTES

Since there is shade variation in all products, the glass tile supplied for your particular installation may not match these samples. Final selection should be made from actual glass tiles and not from glass tile samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Morello is suitable for use in wet areas such as shower walls. During the production process a protective coating is added to the surface of aluminum to provide a rust resistant finish. Also, anti-oxidant oil is applied to ensure quality.

For additional information, refer to "Factors to Consider" at http://americanolean.com/factors-to-consider.cfm.







Naturally, many of our products can help you earn LEED™ credits.

888.AOT.TILE ©2015 AMERICAN OLEAN (09/15)

